

## **HM8362**

HM8362 is a labeling adhesive specially developed for various beverage bottles. It has good initial bonding and wettability, good bonding strength and weather resistance.

## **Product parameters**

•	HM8362
Product	Hot Melt Adhesive
State	Solid
Color	Yellow
Viscosity/mPa.s	500-1000/160℃
Softening point	70±5
Storage life	25°C, Sealed packaging, 24 months
Condition of storage	Store in sealed and cool place, avoid exposure to high temperature or freezing. To be stored between 5 to 35 °C.

Usage

Glue	Nozzle, blade, etc.
Operating temperature	120−160°C
Safety measures	Wear gloves and goggles each time when using the product. Make sure good air circulation around melt box and applicator.

## Reminder

- 1. Keep the bonding area clean without dust and oil.
- 2. Check regularly the thermometer on the machine to see if the temperature is enough, and adjust accordingly.

## Legal provisions

This information is based on laboratory tests and long-term practical experience and outcome. This information is intended to help users to find the most appropriate way to work. As the production conditions from the end users are beyond our control, we cannot be responsible for the work of the user's own production conditions. In any case, it is recommended that appropriate manufacturing process parameters be determined by testing prior to use.



WINLONG GW INTERNATIONAL TECHNOLOGY (QINGDAO) CO., LTD.

Address: NO.46A, South Yantai Road, Wangcheng Street, Laixi

City, Qingdao, Shandong Province, China

Telephone: +86 532 83109100 +86 20 38661234 Fax: +86 532 83100111 +86 20 38661820

Revision date: 202309

1 of 1